

RF CAUTERY SURTRON

2 MHz



SURTRON is a high frequency electro-surgical equipment which is suitable for light and medium surgery.

SURTRON, through its performance allows pure CUT, cut-coagulation BLEND, superficial coagulation (FORCED COAG), deep coagulation and with a special adapter BIPOLAR coagulation. The digital reading of delivered power and the monitoring of operative function by microcontroller guarantees the absolute reliability of working conditions.

TECHNICAL SPECIFICATIONS

Maximum output power CUT (W)	160 → 250? ±20%
Maximum output power BLEND (W)	120 → 200? ±20%
Maximum output power COAG FORCED (W)	100 → 150? ±20%
Maximum output power COAG SOFT (W)	80 → 100? ±20%
Maximum output power BIPOLAR (W)	60 → 100? ±20%
Modulation factor CUT	± 5%
Modulation factor BLEND	± 5%
Modulation factor BIPOLAR	± 5%
Working frequency	600 kHz
Electrical requirements	230V AC, 50 Hz
Weight	5 Kg (Approx)

M/s. Healkeren Medtronics Private Limited

No.4, 2nd Cross, Lakshmipura Main Road, Krishnappa Industrial Estate, Abbigere, Bengaluru - 560 090, Karnataka, India.

Mobile : 93101 18774 / 80882 84888 / 80882 84898, Email : sales@healkeren.com / healkeren@gmail.com / info@healkeren.com

www.healkeren.com